www.tssa.org

Show facsimile of manufacturer's logo or trademark, as it will appear on the fitting, in the space below



	STATU	TORY DECLA Registration of Fitting	Turior,		
I, _Joel Feldman,	Vice President of Engineering				
	(Name and Position	, e.g. President, Plant Manager, C	hief Engineer)		
of Swagelok Con	npany				
		(Name of Manufacturer)			
Located at 295	00 Solon Road, Solon, Ohio 44139	USA	(440) 248-4600	(440) 349-5970	
(Plant Address)			(Telephone No.)	(Fax No.)	
✓ do solemnly declare that the fittings listed hereunder, which are subject to the Technical Standards and Safety Act, Boilers and Pressure Vessels Regulation, comply with all of the requirements of ASME B31.1 for unlisted components, and ASME B31.3 for unlisted components					
		cognized North American Standard			
which specif	ies the dimensions, materials of constru	ction, pressure/temperature ra	tings, identification marki	ng the fittings and service;	
pressure/te	mperature ratings and the basis for su at the manufacture of these fittings is	rted by the attached data whi uch ratings, the marking of the controlled by a quality syste	ch identifies the dimension ne fitting for identification	ons, material of construction, and service.	
77-3	_ which has been verified by the following				
	by this declaration, for which I seek regist		g.	type fittings. In support of	
	following information and/or test data are ¢ertificate, Attachment A, Attachmen		nd other Support Docu	ments	
		ings, calculations, test reports, etc.			
Declared before	me at	in the		of	
the	day ofAl	D 20			
Commissioner fo	or Oaths:		DocuSigned by:	_	
	o get a notary signa College Penter   D-19 situation		fool (	24-	
	(Signature)		C87CBBFFD3F14 (Signature of	4/2/2021   8:11 IB7 Declarer)	
	FO	R OFFICE USE ONLY			
Technical Standar	nowledge and belief, the application m rds and Safety Act, Boilers and Press and is accepted for registration in Cate	eets the requirements of the ure Vessels Regulation, and	Technical Standards and Safety Authority	Boilers and Pressure Vessels Safety Program	
CRN:	0A23291.5	This		STERED	
Registered by:	LILIANA CONSTANTINE	"TRRA" signed	Signad:	.5	
Dated:	JUNE 1, 2021	The sta size has optimize	s been Date: June 1,	2021.	
NOTE: This regis	stration expires on: <u>JUNE 1,</u>	2031 docume	nts		



THIS IS PART OF CRN
0A23291.5
Technical Standards and Safety Authority
Boilers and Pressure Vessels Safety

Date: March 8, 2021 Page 1 of 3

# Attachment B. Scope of Registration for Swagelok Alloy 825 (ASTM B425 UNS N08825) Tube Fittings (Category A)

This document presents the scope of Swagelok Nickel-Chromium Alloy 825 Tube Fittings covered by this submission for CRN approval. These fittings have been evaluated in accordance with ASME B31.1-2020 and ASME B31.3-2018 for unlisted components.

The fittings rating is based on the lower rating between the type of end connections. Summary Table

	Material (Standard)	Port Connections and Sizes	Maximum Allowable Working Pressure			
Product Description or Series			Up to 100°F (psig)	At maximum temperature per ASME B31.3 (psig)	At maximum temperature per ASME B31.1 (psig)	Design Code of Construction
Gaugeable Tube Fittings and Adapter Fittings	Alloy 825, UNS N08825 (ASTM B425) For straight fittings, hardware Alloy 825, UNS N08825 (ASTM B564) For shaped fittings	Tube Fitting 1/4 - 1/2 inch, 6 - 12mm	See Table below	See Table below	See Table below	Unlisted Component in ASME B31.1 & B31.1
		NPT, Male 1/16 - 1 inch	11 600 - 6100	11 449 – 6021* at 800°F (426°C)	8468 - 4453* at 800°F (426°C)	ASME B1.20.1 is listed in
		NPT, Female 1/16 - 1 inch	7800 - 5100	7699 - 5034* at 800°F (426°C)	5694 - 3723* at 800°F (426°C)	ASME B31.1 & B31.3

<sup>\*\*</sup>Rating for fitting material (may be limited by thread sealant)

#### Alloy 825 Swagelok Tube Fitting Pressure Rating Tables

	Maximum Allowable Working Pressure				
Swagelok End Connection Size	Up to 100°F	At maximum temp. 800°F (426°C) per ASME B31.3	At maximum temp. 800°F (426°C) per ASME B31.1		
1/4 inch	11600 psig	11 449 psig	8468 psig		
3/8 inch	8200 psig	8093 psig	5986 psig		
1/2 inch	5900 psig	5823 psig	4307 psig		
6 mm	660 bar	651 bar	482 bar		
10 mm	480 bar	474 bar	350 bar		
12 mm	480 bar	474 bar	350 bar		



Canadian Registration Number Submittal Category A: Swagelok Alloy 825 Tube Fittings

#### **Product Description**

Swagelok Fittings are furnished in a variety of configurations and shapes (straight, elbow, or tee). Swagelok Fittings consist of at least one Swagelok End – a two-ferrule mechanical-grip design. The Swagelok end is a proprietary design, and the assembly consists of Swagelok body, nut, front and back ferrule (see detail). The table above, as well as the "Configurations" section, covers a variety of other end connections.







Date: March 8, 2021


Page 2 of 3

### **Configurations**


Unions (Straight, Elbow, Tee)
 Swagelok Tube Fitting End Connections










2. Male and Female Connectors / Adapters (Straight, Elbow, Tee)
Swagelok Tube Fitting End Connection to an NPT End Connection









Swagelok to NPT Male Connectors

Swagelok to NPT Female Connectors

(For dimensions see catalog.)



Canadian Registration Number Submittal Category A: Swagelok Alloy 825 Tube Fittings

# **Product Options:**

The product options listed below affect pressure and/or temperature ratings shown in the above Summary Table, but in all cases the ratings are less than, or equal to, those shown in the table.

Date: March 8, 2021

Page 3 of 3

- 1. Bored-Through Fittings.
- 2. Sealant for tapered pipe threads (NPT):
  - a. Curable resin with PTFE
  - b. PTFE tape

Additional options that do not affect pressure and/or temperature ratings may be made available within the scope of this approval. Examples of these would include the following:

- 1. Special marking
- 2. Special cleaning
- 3. Wire drills
- 4. Bulkhead Configurations
- 5. Snubbers/frits and orifice plates
- 6. Equivalent metric or fractional hex sizes

All the above options, those that affect pressure and/or temperature ratings and those that do not, are within the scope of this approval.

#### **Quality System**

The Swagelok Company quality system complies with the requirements of ISO 9001:2015. The Swagelok Company maintains BSI Certificate of Registration Number FM 01729, which applies to all locations listed on the Certificate.

#### References

The product catalog does not represent the full scope of the registration but rather details some of the most common options.

- Gaugeable Tube Fittings and Adapter Fittings MS-01-140, Rev AE
- Swagelok Tubing Data Sheet MS-01-107, Rev T

# THIS IS PART OF CRN

0A23291.5

Technical Standards and Safety Authority
Boilers and Pressure Vessels Safety
Program

# Attachment A. Swagelok Manufacturing Locations

This document lists the Swagelok locations where end item or component level manufacturing activities take place.

	<u> </u>
Swagelok Company	Swagelok Company (Falon 1)
29500 Solon Road	348 Bishop Road
Solon, Ohio 44139	Highland Heights, Ohio 44143
USA	USA
Swagelok Company (Highland)	Swagelok Company (Falon 2)
318 Bishop Road	358 Bishop Road
Highland Heights, Ohio 44143	Highland Heights, Ohio 44143
USA	USA
Swagelok Company (OFC)	Swagelok Company (HPF)
29495 F.A. Lennon Drive	6050 Cochran Road
Solon, Ohio 44139	Solon, Ohio 44139
USA	USA
Swagelok Company (Atlantic)	Swagelok Company (Snow Metal)
26651 Curtiss Wright Parkway	6060 Cochran Road
Willoughby Hills, Ohio 44092	Solon, Ohio 44139
USA	USA
Swagelok Company (Micro) 26653 Curtiss Wright Parkway Willoughby Hills, Ohio 44092 USA	Swagelok Company (Alfred) 29500 Ambina Drive Solon, Ohio 44139
Swagelok Hose Services Company (SHSC)	Swagelok Company (Strongsville)
29900 Solon Industrial Parkway	15400 Foltz Road
Solon, Ohio 44139	Strongsville, Ohio 44119
Swagelok (China) Fluid System Technologies Ltd. Changshu Export Process Zone Changshu Economic Development Zone Changshu, Jiangshu 215513 China	Swagelok Limited Ballafletcher Road Tromode IM4 4RA Isle of Man